

Garant

Solid carbide roughing end mill MTC / TPC, TiAlN, Ø f8 DC: 16 mm



Order data

Order number	202979 16
GTIN	4062406245412
Item class	11X

Description

Version:

Significant cutting force reduction due to 45° helix.

Application:

Especially for **MTC (Multi Task Cutting)** use on the new generation of turning / milling centres.

Note:

For materials > 55 HRC we recommend reducing the depth of cut to $a_p = 0.25 \times D \dots 0.5 \times D$.

Tolerance nominal Ø: f8

No. of teeth Z: 4

Helix angle: 45 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

No. of teeth Z: 4

Flute length L_c : 36 mm

Overhang length L_1 incl. recess: 40 mm

Recess Ø D_1 : 15 mm

Overall length L: 92 mm

Shank Ø D_s : 16 mm

Technical description

Recess Ø D_1	15 mm
Overall length L	92 mm
No. of teeth Z	4
Helix angle	45 degrees
Feed f_z for slot milling in steel < 60 HRC	0.04 mm

Cutting edge $\varnothing D_c$	16 mm
Direction of infeed	horizontal, oblique and vertical
Tolerance nominal \varnothing	f8
Shank $\varnothing D_s$	16 mm
Feed f_z for side milling in steel < 60 HRC	0.045 mm
Flute length L_c	36 mm
Shank	DIN 6535 HA to h6
Overhang length L_1 incl. recess	40 mm
Corner rounding r_v	0.3 mm
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	H
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	0.1×D
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Cutting width a_e for milling operation	0.15×D for side milling
Through-coolant	no
Machining strategy	MTC
Machining strategy	TPC
Colour ring	red
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 16 mm	SZ2025 16

