

Garant**GARANT Master INOX solid carbide milling cutter HPC / TPC, TiAlN, Ø h10 DC: 4 mm****Order data**

Order number	202997 4
GTIN	4062406231569
Item class	11X

Description**Version:**

For **roughing and finishing**.

HPC milling cutter with **newly developed high-performance coating** for **outstanding tool life** and **optimum metal removal rate** in a very wide range of stainless steels. **Greater oxidation resistance** and **high-temperature hardness**.

Can be used at **high cutting speeds**, particularly suitable even for TOOLOX®.

Advantage:

Particularly low vibration running.

Tolerance nominal Ø: h10

No. of teeth Z: 4

Helix angle: 40 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 4

Flute length L_c: 11 mm

Overhang length L₁ incl. recess: 21 mm

Recess Ø D₁: 3.8 mm

Overall length L: 57 mm

Shank Ø D_s: 6 mm

Technical description

Tolerance nominal Ø	h10
Overhang length L ₁ incl. recess	21 mm
No. of teeth Z	4

Feed f_z for slot milling in stainless steel $> 900 \text{ N/mm}^2$	0.012 mm
Recess $\varnothing D_1$	3.8 mm
Shank $\varnothing D_s$	6 mm
Helix angle	40 degrees
Overall length L	57 mm
Direction of infeed	horizontal, oblique and vertical
Flute length L_c	11 mm
Shank	DIN 6535 HB to h6
Cutting edge $\varnothing D_c$	4 mm
Feed f_z for side milling in INOX $> 900 \text{ N/mm}^2$	0.015 mm
Corner chamfer width at 45°	0.1 mm
Corner chamfer angle	45 degrees
Series	GARANT Master INOX
Coating	TiAlN
Tool material	solid carbide
Standard	DIN 6527
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Cutting width a_e for milling operation	$0.1 \times D$
Through-coolant	no
Machining strategy	TPC
Machining strategy	HPC
Colour ring	blue
Type of product	End mill