

Garant

GARANT Master Titan solid carbide milling cutter HPC, TiAlN, Ø DC: 10 mm



Order data

Order number	203029 10
GTIN	4045197991782
Item class	11Z

Description

Version:

Specially ground with **corner radii similar to torus cutters.**

Application:

For milling **titanium and titanium alloys**, with very smooth cutting action for optimum tool lives and top metal removal rate.

Tolerance nominal Ø: e8

No. of teeth Z: 4

Helix angle: 40 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

No. of teeth Z: 4

Flute length L_c : 22 mm

Overhang length L_1 incl. recess: 32 mm

Recess Ø D_1 : 9.7 mm

Overall length L: 72 mm

Shank Ø D_s : 10 mm

Technical description

Overhang length L_1 incl. recess	32 mm
Feed f_z for side milling in titanium > 850 N/mm ²	0.042 mm
Shank Ø D_s	10 mm
Feed f_z for slot milling in titanium > 850 N/mm ²	0.034 mm
Cutting edge Ø D_c	10 mm

Recess $\varnothing D_1$	9.7 mm
No. of teeth Z	4
Direction of infeed	horizontal, oblique and vertical
Helix angle	40 degrees
Tolerance nominal \varnothing	e8
Shank	DIN 6535 HA to h6
Flute length L_c	22 mm
Overall length L	72 mm
Corner rounding r_v	0.2 mm
Series	GARANT Master Titan
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Cutting width a_e for milling operation	$0.3 \times D$ for side milling
Through-coolant	no
Machining strategy	HPC
Colour ring	pink
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------