

Garant
GARANT Master Titan solid carbide milling cutter HPC, TiAlN, Ø DC: 16 mm

Order data

Order number	203029 16
GTIN	4045197991805
Item class	11Z

Description
Version:

Specially ground with **corner radii similar to torus cutters.**

Application:

For milling **titanium and titanium alloys**, with very smooth cutting action for optimum tool lives and top metal removal rate.

Tolerance nominal Ø: e8

No. of teeth Z: 4

Helix angle: 40 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

No. of teeth Z: 4

Flute length L_c : 32 mm

Overhang length L_1 incl. recess: 44 mm

Recess Ø D_1 : 15.5 mm

Overall length L: 92 mm

Shank Ø D_s : 16 mm

Technical description

Recess Ø D_1	15.5 mm
Shank Ø D_s	16 mm
Feed f_z for slot milling in titanium > 850 N/mm ²	0.05 mm
Feed f_z for side milling in titanium > 850 N/mm ²	0.065 mm
Helix angle	40 degrees

Shank	DIN 6535 HA to h6
Flute length L_c	32 mm
Direction of infeed	horizontal, oblique and vertical
Cutting edge $\varnothing D_c$	16 mm
Overall length L	92 mm
Overhang length L_1 incl. recess	44 mm
No. of teeth Z	4
Tolerance nominal \varnothing	e8
Corner rounding r_v	0.3 mm
Series	GARANT Master Titan
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Cutting width a_e for milling operation	$0.3 \times D$ for side milling
Through-coolant	no
Machining strategy	HPC
Colour ring	pink
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------