

Garant

GARANT Master Steel solid carbide roughing end mill HPC, TiAlN, Ø f8 DC: 16 mm



Order data

Order number	203039 16
GTIN	4062406230951
Item class	11X

Description

Version:

For **roughing and finishing**.

Up to 1.5xD into solid material **at very high feed rates** with smooth cutting action.

Advantage:

Optimised flute form, eccentric relief ground, generous chip spaces.

Tolerance nominal Ø: f8

No. of teeth Z: 4

Helix angle: 38 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 4

Flute length L_c : 36 mm

Overhang length L_1 incl. recess: 42 mm

Recess Ø D_1 : 15.8 mm

Overall length L: 92 mm

Shank Ø D_s : 16 mm

Technical description

Corner chamfer width at 45°	0.1 mm
Shank Ø D_s	16 mm
No. of teeth Z	4
Recess Ø D_1	15.8 mm
Helix angle	38 degrees

Direction of infeed	horizontal, oblique and vertical
Overall length L	92 mm
Flute length L_c	36 mm
Feed f_z for slot milling in steel < 900 N/mm ²	0.08 mm
Tolerance nominal \varnothing	f8
Shank	DIN 6535 HB to h6
Feed f_z for side milling in steel < 900 N/mm ²	0.1 mm
Overhang length L_1 incl. recess	42 mm
Cutting edge $\varnothing D_c$	16 mm
Corner chamfer angle	45 degrees
Series	GARANT Master Steel
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	Full slot cutting depth 1xD
Cutting width a_e for milling operation	0.03xD for copy milling
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill

Services

Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 16 mm

SZ2025 16