

Garant
GARANT Master Ni-Based solid carbide milling cutter HPC / TPC, TiAlN, Ø DC: 8 mm

Order data

Order number	203048 8
GTIN	4062406565725
Item class	11Z

Description
Version:

Specially ground with **corner radii similar to torus cutters**.

Innovative substrate specially for machining **nickel-based alloys**. Newly developed coating.

Application:

For milling **nickel-based alloys with high red hardness**.

Note:

Successor product to No. 203028.

Tolerance nominal Ø: e8

No. of teeth Z: 4

Helix angle: 35 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 4

Flute length L_c : 21 mm

Overhang length L_1 incl. recess: 13 mm

Recess Ø D_1 : 7.7 mm

Overall length L: 63 mm

Shank Ø D_s : 8 mm

Technical description

Corner rounding r_v	0.2 mm
Feed f_z for side milling in Inconel®	0.065 mm
Shank	DIN 6535 HB to h6

Helix angle	35 degrees
Overall length L	63 mm
Overhang length L ₁ incl. recess	13 mm
Flute length L _c	21 mm
Direction of infeed	horizontal, oblique and vertical
Tolerance nominal Ø	e8
Cutting edge Ø D _c	8 mm
No. of teeth Z	4
Shank Ø D _s	8 mm
Recess Ø D ₁	7.7 mm
Series	GARANT Master Titan
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Spacing of the cutters	unequal spacing
Cutting width a _e for milling operation	0,08×D
Through-coolant	no
Machining strategy	TPC
Machining strategy	HPC
Colour ring	pink
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------