

# GARANT Master UNI solid carbide roughing end mill HPC, TiSiN, Ø e8 DC: 3 mm



#### Order data

Order number	203062 3
GTIN	4062406569525
Item class	11Z

## **Description**

#### **Version:**

For **roughing and finishing at very high feed rates** with smooth cutting action. **Newly developed geometry and high-performance coating** for outstanding production results and very long tool life with a variety of materials. Unequal spacing gives **high intrinsic stability** and smooth cutting action.

### **Advantage:**

- · Particularly low vibration running.
- · Special flute profile, large flutes.
- Specially matched edge honing.
- · Optimised substrate for hardness and toughness.

Tolerance nominal Ø: e8

No. of teeth Z: 4

Helix angle: 42 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 4 Flute length L<sub>c</sub>: 5 mm

Overhang length L<sub>1</sub> incl. recess: 10 mm

Recess  $\emptyset$  D<sub>1</sub>: 2.8 mm Overall length L: 50 mm Shank  $\emptyset$  D<sub>4</sub>: 6 mm

## **Technical description**

Feed $f_z$ for side milling in steel < 900 N/mm <sup>2</sup>	0.025 mm
--	----------

Helix angle	42 degrees
Direction of infeed	horizontal, oblique and vertical
Feed $f_z$ for side milling in INOX > 900 N/mm <sup>2</sup>	0.015 mm
Flute length L <sub>c</sub>	5 mm
Feed $f_z$ for slot milling in stainless steel > 900 N/mm <sup>2</sup>	0.012 mm
Feed f <sub>z</sub> for slot milling in steel < 900 N/mm <sup>2</sup>	0.02 mm
Corner rounding r <sub>v</sub>	0.1 mm
Shank	DIN 6535 HB to h6
Overhang length L₁ incl. recess	10 mm
Shank Ø D <sub>s</sub>	6 mm
Cutting edge $\emptyset$ D <sub>c</sub>	3 mm
Tolerance nominal ∅	e8
Overall length L	50 mm
Recess Ø D <sub>1</sub>	2.8 mm
No. of teeth Z	4
Series	GARANT Master UNI
Coating	TiSiN
Tool material	solid carbide
Standard	Manufacturer's standard
Туре	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a <sub>e</sub> for milling operation	Full slot cutting depth 1×D
Cutting width a <sub>e</sub> for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill

