



HOLEX Pro UNI solid carbide roughing end mill HPC, TiSiN, Ø e8 DC: 16 mm

Order data

Order number	203063 16
GTIN	4062406569068
Item class	12Y

Description
Version:

For **roughing and finishing** up to $1.5 \times D$ into solid material **at very high feed rates** with smooth cutting action.

For cutting force reduction and better surface quality due to **45° helix**.

Tolerance nominal Ø: e8

No. of teeth Z: 4

Helix angle: 42 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 4

Flute length L_c : 22 mm

Overhang length L_1 incl. recess: 32 mm

Recess Ø D_1 : 15.5 mm

Overall length L: 82 mm

Shank Ø D_s : 16 mm

Technical description

Feed f_z for slot milling in stainless steel $> 900 \text{ N/mm}^2$	0.05 mm
Helix angle	42 degrees
Corner chamfer angle	45 degrees
Direction of infeed	horizontal, oblique and vertical
Feed f_z for side milling in INOX $> 900 \text{ N/mm}^2$	0.06 mm

Overall length L	82 mm
Tolerance nominal Ø	e8
Cutting edge Ø D _c	16 mm
Shank Ø D _s	16 mm
Flute length L _c	22 mm
No. of teeth Z	4
Feed f _z for side milling in steel < 900 N/mm ²	0.1 mm
Overhang length L ₁ incl. recess	32 mm
Recess Ø D ₁	15.5 mm
Shank	DIN 6535 HB to h6
Feed f _z for slot milling in steel < 900 N/mm ²	0.08 mm
Corner chamfer width at 45°	0.3 mm
Series	HOLEX Pro UNI
Coating	TiSiN
Tool material	solid carbide
Standard	Manufacturer's standard
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a _e for milling operation	Full slot cutting depth 1×D
Cutting width a _e for milling operation	0.3×D for side milling
Through-coolant	no
Machining strategy	MTC
Colour ring	green
Type of product	End mill