



HOLEX Pro UNI solid carbide roughing end mill HPC, TiSiN, Ø e8 DC: 8 mm

Order data

Order number	203063 8
GTIN	4062406569747
Item class	12Y

Description
Version:

For **roughing and finishing** up to $1.5 \times D$ into solid material **at very high feed rates** with smooth cutting action.

For cutting force reduction and better surface quality due to **45° helix**.

Tolerance nominal Ø: e8

No. of teeth Z: 4

Helix angle: 42 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 4

Flute length L_c : 12 mm

Overhang length L_1 incl. recess: 20 mm

Recess Ø D_1 : 7.7 mm

Overall length L: 58 mm

Shank Ø D_s : 8 mm

Technical description

Recess Ø D_1	7.7 mm
Shank Ø D_s	8 mm
Corner chamfer width at 45°	0.2 mm
Feed f_z for side milling in INOX > 900 N/mm ²	0.03 mm
Cutting edge Ø D_c	8 mm

Corner chamfer angle	45 degrees
Feed f_z for slot milling in steel $< 900 \text{ N/mm}^2$	0.05 mm
Flute length L_c	12 mm
No. of teeth Z	4
Feed f_z for slot milling in stainless steel $> 900 \text{ N/mm}^2$	0.025 mm
Direction of infeed	horizontal, oblique and vertical
Overhang length L_1 incl. recess	20 mm
Helix angle	42 degrees
Feed f_z for side milling in steel $< 900 \text{ N/mm}^2$	0.06 mm
Overall length L	58 mm
Tolerance nominal $\varnothing$	e8
Shank	DIN 6535 HB to h6
Series	HOLEX Pro UNI
Coating	TiSiN
Tool material	solid carbide
Standard	Manufacturer's standard
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Cutting width a_e for milling operation	$0.3 \times D$ for side milling
Through-coolant	no
Machining strategy	MTC
Colour ring	green
Type of product	End mill