


Solid carbide milling cutter with chip separators TPC, TiSiN, Ø e8 DC: 10 mm

Order data

Order number	203085 10
GTIN	4062406569334
Item class	12X

Description
Version:

High-performance end mill for general-purpose applications, **specially designed for TPC applications.**

Strengthened core.

Optimised bending strength due to the use of ultra-fine grain substrates.

Chip breaker for controlled chip breaking.

Note:

h_{max} : The values stated in the table are maximum values.

$a_{e\ max} = 0.18 \times D$ for TPC machining.

Tolerance nominal Ø: e8

No. of teeth Z: 4

Helix angle: 40 degrees

Direction of infeed: horizontal and oblique

Shank: DIN 6535 HB to h6

Balance quality with shank: G 2.5 with HB

No. of teeth Z: 4

Flute length L_c : 30 mm

Overhang length L_1 incl. recess: 35 mm

Recess Ø D_1 : 9.8 mm

Overall length L: 80 mm

Shank Ø D_s : 10 mm

Technical description

Shank	DIN 6535 HB to h6
Overall length L	80 mm

Direction of infeed	horizontal and oblique
Cutting edge Ø D _c	10 mm
No. of teeth Z	4
Tolerance nominal Ø	e8
Helix angle	40 degrees
Corner chamfer angle	45 degrees
Balance quality with shank	G 2.5 with HB
Shank Ø D _s	10 mm
Corner chamfer width at 45°	0.2 mm
Recess Ø D ₁	9.8 mm
Overhang length L ₁ incl. recess	35 mm
Flute length L _c	30 mm
Average chip thickness h _{max} for TPC milling in steel < 900 N/mm ²	0.074 mm
Coating	TiSiN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a _e for milling operation	0.18×D
Through-coolant	no
Machining strategy	TPC
Colour ring	green
Type of product	End mill