

Garant

Solid carbide milling cutter TPC, TiAlN, Ø f8 DC: 16 mm



Order data

Order number	203088 16
GTIN	4045197814302
Item class	11X

Description

Version:

High-performance milling cutter specially designed for general-purpose TPC applications.

Strengthened core.

Optimised bending strength due to the use of ultra-fine grain substrates.

Note:

$a_{e\max} = 0.1 \times D$ for TPC machining.

h_{\max} : The values stated in the table are maximum values.

Tolerance nominal Ø: f8

No. of teeth Z: 5

Helix angle: 40 degrees

Direction of infeed: horizontal and oblique

Shank: DIN 6535 HB to h6

Balance quality with shank: G 2.5 with HB

No. of teeth Z: 5

Flute length L_c : 32 mm

Overhang length L_1 incl. recess: 42 mm

Recess Ø D_1 : 15.8 mm

Overall length L: 92 mm

Shank Ø D_s : 16 mm

Technical description

Tolerance nominal Ø	f8
Shank Ø D_s	16 mm
Shank	DIN 6535 HB to h6

Overall length L	92 mm
No. of teeth Z	5
Recess $\varnothing D_1$	15.8 mm
Direction of infeed	horizontal and oblique
Average chip thickness h_{\max} for TPC milling in Toolox 44 HRC	0.085 mm
Flute length L_c	32 mm
Corner chamfer width at 45°	0.32 mm
Balance quality with shank	G 2.5 with HB
Cutting edge $\varnothing D_c$	16 mm
Overhang length L_1 incl. recess	42 mm
Helix angle	40 degrees
Corner chamfer angle	45 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	$0.1 \times D$
Through-coolant	no
Machining strategy	TPC
Colour ring	green
Type of product	End mill

Services

Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 16 mm

SZ2025 16