

**Garant**
**Solid carbide milling cutter with chip separators TPC, TiAlN, Ø f8 DC: 20 mm**

**Order data**

Order number	203091 20
GTIN	4045197814449
Item class	11X

**Description**
**Version:**

High-performance end mills for general-purpose machining, **specially designed for TPC applications.**

Strengthened core. Offset chip breaker. **Optimised bending strength** due to the use of ultra-fine grain substrates.

**Note:**

$h_{max}$ : The values stated in the table are maximum values.

$a_{e,max} = 0.03 \times D$  for TPC machining.

Tolerance nominal Ø: f8

No. of teeth Z: 5

Helix angle: 40 degrees

Direction of infeed: horizontal and oblique

Shank: DIN 6535 HB to h6

Balance quality with shank: G 2.5 with HB

No. of teeth Z: 5

Flute length  $L_c$ : 100 mm

Overall length L: 160 mm

Shank Ø  $D_s$ : 20 mm

Corner chamfer width at 45°: 0.4 mm

Average chip thickness  $h_{max}$  for TPC milling in Toolox 44 HRC: 0.07 mm

**Technical description**

Flute length $L_c$	100 mm
Average chip thickness $h_{max}$ for TPC milling in Toolox 44 HRC	0.07 mm

No. of teeth Z	5
Shank $\varnothing D_s$	20 mm
Balance quality with shank	G 2.5 with HB
Corner chamfer width at 45°	0.4 mm
Tolerance nominal $\varnothing$	f8
Shank	DIN 6535 HB to h6
Cutting edge $\varnothing D_c$	20 mm
Direction of infeed	horizontal and oblique
Overall length L	160 mm
Helix angle	40 degrees
Corner chamfer angle	45 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width $a_e$ for milling operation	0.03×D
Through-coolant	no
Machining strategy	TPC
Colour ring	green
Type of product	End mill

## Services

Shank clamping flats for shrink-fit chucks, with retainer function Shank  $\varnothing$  tool 20 mm

SZ2025 20