

Garant

GARANT Master Alu solid carbide milling cutter with more chip separators TPC, DLC, Ø h6 DC: 6 mm



Order data

Order number	203113 6
GTIN	4062406245757
Item class	11X

Description

Version:

Specially designed for TPC high-performance milling. **Optimised bending strength** due to the use of ultra-fine grain substrates. **1xD** chip separator for controlled chip breaking.

Balanced for very high process reliability and protecting the machine at high speeds.

Application:

Especially for milling **aluminium and non-ferrous metals**.

Note:

h_{max} : The values stated in the table are maximum values.

$ae_{max} = 0.15 \times D$ for TPC machining.

Tolerance nominal \varnothing : h6

No. of teeth Z: 4

Helix angle: 38 degrees

Direction of infeed: horizontal and oblique

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 4

Flute length L_c : 18 mm

Overhang length L_1 incl. recess: 25 mm

Recess $\varnothing D_1$: 5.5 mm

Overall length L: 65 mm

Shank $\varnothing D_s$: 6 mm

Technical description

Average chip thickness h_{max} for TPC milling in short-chipping aluminium

0.043 mm

Tolerance nominal \varnothing	h6
Direction of infeed	horizontal and oblique
Cutting edge $\varnothing D_c$	6 mm
Shank	DIN 6535 HA to h6
Flute length L_c	18 mm
No. of teeth Z	4
Shank $\varnothing D_s$	6 mm
Overall length L	65 mm
Shank form	HA
Helix angle	38 degrees
Recess $\varnothing D_1$	5.5 mm
Overhang length L_1 incl. recess	25 mm
Balance quality with shank	G 2.5 with HA
Corner rounding r_v	0.05 mm
Series	GARANT Master Alu
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	0.15×D
Through-coolant	no
Machining strategy	TPC
Colour ring	yellow
Type of product	End mill