

## Garant

### GARANT Master Alu solid carbide milling cutter with more chip separators TPC, DLC, Ø h6 DC: 8 mm



#### Order data

Order number	203113 8
GTIN	4062406245764
Item class	11X

#### Description

##### Version:

**Specially designed for** TPC high-performance milling. **Optimised bending strength** due to the use of ultra-fine grain substrates. **1xD** chip separator for controlled chip breaking.

**Balanced** for very high process reliability and protecting the machine at high speeds.

##### Application:

Especially for milling **aluminium and non-ferrous metals**.

##### Note:

$h_{max}$ : The values stated in the table are maximum values.

$ae_{max} = 0.15 \times D$  for TPC machining.

Tolerance nominal  $\varnothing$ : h6

No. of teeth Z: 4

Helix angle: 38 degrees

Direction of infeed: horizontal and oblique

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 4

Flute length  $L_c$ : 24 mm

Overhang length  $L_1$  incl. recess: 30 mm

Recess  $\varnothing D_1$ : 7.5 mm

Overall length L: 70 mm

Shank  $\varnothing D_s$ : 8 mm

#### Technical description

Direction of infeed	horizontal and oblique
---------------------	------------------------

Helix angle	38 degrees
Average chip thickness $h_{\max}$ for TPC milling in short-chipping aluminium	0.057 mm
No. of teeth Z	4
Recess $\varnothing D_1$	7.5 mm
Cutting edge $\varnothing D_c$	8 mm
Tolerance nominal $\varnothing$	h6
Overall length L	70 mm
Overhang length $L_1$ incl. recess	30 mm
Shank	DIN 6535 HA to h6
Shank $\varnothing D_s$	8 mm
Balance quality with shank	G 2.5 with HA
Shank form	HA
Flute length $L_c$	24 mm
Corner rounding $r_v$	0.1 mm
Series	GARANT Master Alu
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Spacing of the cutters	unequal spacing
Cutting width $a_e$ for milling operation	0.15×D
Through-coolant	no
Machining strategy	TPC
Colour ring	yellow
Type of product	End mill