

## Garant

### GARANT Master Alu solid carbide milling cutter, HPC HPC, DLC, Ø e8 DC: 16 mm



#### Order data

Order number	203205 16
GTIN	4062406120016
Item class	11X

#### Description

##### Version:

For finishing operations.

Special geometry for optimum chip evacuation.

Unequal spacing gives high intrinsic stability and smooth cutting action.

For profile milling as a finishing operation.

Tolerance nominal Ø: e8

No. of teeth Z: 5

Helix angle: 38 degrees

Direction of infeed: horizontal

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 5

Flute length  $L_c$ : 80 mm

Overhang length  $L_1$  incl. recess: 88 mm

Recess Ø  $D_1$ : 15.5 mm

Overall length L: 134 mm

Shank Ø  $D_s$ : 16 mm

#### Technical description

Overhang length $L_1$ incl. recess	88 mm
Balance quality with shank	G 2.5 with HA
No. of teeth Z	5
Tolerance nominal Ø	e8

Correction factor $f_z$	1.5
Overall length L	134 mm
Cutting edge $\varnothing D_c$	16 mm
maximum cutting depth $a_{p_{max}}$ when side milling	80 mm
Recess $\varnothing D_1$	15.5 mm
Shank $\varnothing D_s$	16 mm
Flute length $L_c$	80 mm
Direction of infeed	horizontal
Shank	DIN 6535 HA to h6
Feed $f_z$ for side milling in short-chipping aluminium	0.06 mm
maximum cutting depth $a_{p_{max}}$ when slot milling from solid	16 mm
Helix angle	38 degrees
Corner chamfer angle	90 degrees
Series	GARANT Master Alu
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Spacing of the cutters	unequal spacing
Cutting width $a_e$ for milling operation	$0.05 \times D$ for side milling
Through-coolant	no
Machining strategy	HPC
Shank tolerance	h6
Colour ring	yellow
Type of product	End mill

## Services

Shank grinding Type HB	129100 HB
------------------------	-----------

