

Garant
GARANT Master Alu solid carbide milling cutter, HPC HPC, uncoated, Ø e8 DC: 8 mm

Order data

Order number	203208 8
GTIN	4062406565923
Item class	11X

Description
Version:

For finishing operations.

Special geometry for optimum chip evacuation.

Unequal spacing gives high intrinsic stability and smooth cutting action.

For profile milling as a finishing operation.

Tolerance nominal Ø: e8

No. of teeth Z: 5

Helix angle: 38 degrees

Direction of infeed: horizontal

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 5

Flute length L_c : 32 mm

Overhang length L_1 incl. recess: 40 mm

Recess Ø D_1 : 7.8 mm

Overall length L: 75 mm

Shank Ø D_s : 8 mm

Technical description

Cutting edge Ø D_c	8 mm
Shank Ø D_s	8 mm
Flute length L_c	32 mm
Corner chamfer angle	90 degrees

Feed f_z for side milling in short-chipping aluminium	0.05 mm
Recess $\varnothing D_1$	7.8 mm
Helix angle	38 degrees
Shank	DIN 6535 HA to h6
Overhang length L_1 incl. recess	40 mm
Tolerance nominal $\varnothing$	e8
No. of teeth Z	5
Direction of infeed	horizontal
Overall length L	75 mm
Balance quality with shank	G 2.5 with HA
Series	GARANT Master Alu
Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	$0.1 \times D$ for side milling
Through-coolant	no
Machining strategy	HPC
Colour ring	yellow
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------