

Garant**GARANT Master Alu solid carbide milling cutter, HPC HPC, uncoated, Ø e8 DC: 16 mm****Order data**

Order number	203209 16
GTIN	4062406566005
Item class	11X

Description**Version:**

For finishing operations.

Special geometry for optimum chip evacuation.

Unequal spacing gives high intrinsic stability and smooth cutting action.

For profile milling as a finishing operation.

Tolerance nominal Ø: e8

No. of teeth Z: 5

Helix angle: 38 degrees

Direction of infeed: horizontal

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 5

Flute length L_c: 80 mm

Overhang length L₁ incl. recess: 88 mm

Recess Ø D₁: 15.5 mm

Overall length L: 134 mm

Shank Ø D_s: 16 mm

Technical description

Shank	DIN 6535 HA to h6
Corner chamfer angle	90 degrees
Overall length L	134 mm
Helix angle	38 degrees

Tolerance nominal $\varnothing$	e8
Flute length L_c	80 mm
Recess $\varnothing D_1$	15.5 mm
No. of teeth Z	5
Direction of infeed	horizontal
Cutting edge $\varnothing D_c$	16 mm
Shank $\varnothing D_s$	16 mm
Feed f_z for side milling in short-chipping aluminium	0.06 mm
Overhang length L_1 incl. recess	88 mm
Balance quality with shank	G 2.5 with HA
Series	GARANT Master Alu
Coating	uncoated
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	$0.05 \times D$ for side milling
Through-coolant	no
Machining strategy	HPC
Colour ring	yellow
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------