


Solid carbide milling cutter, TiAlN, Ø h10 DC: 16 mm

Order data

Order number	203248 16
GTIN	4062406253851
Item class	12X

Description
Version:

Strengthened core and geometry for hard machining, without dynamic helical pitch. Tolerance:
Size nominal Ø D_c **0/-0.02 mm.**

Application:

For profile milling as finishing.

(Plunge cutting only to shallow depths).

Through-coolant: no

Tolerance nominal Ø: 0 / -0.02

No. of teeth Z: 6

Helix angle: 45 degrees

Direction of infeed: horizontal and oblique

Shank: DIN 6535 HA to h6

No. of teeth Z: 6

Flute length L_c: 48 mm

Overall length L: 108 mm

Shank Ø D_s: 16 mm

Corner chamfer width at 45°: 0.16 mm

Feed f_z for side milling in steel < 55 HRC: 0.05 mm

Technical description

Cutting edge Ø D _c	16 mm
Overall length L	108 mm
Flute length L _c	48 mm
Corner chamfer width at 45°	0.16 mm

Direction of infeed	horizontal and oblique
Tolerance nominal \varnothing	0 / -0.02
Shank $\varnothing D_s$	16 mm
Shank	DIN 6535 HA to h6
No. of teeth Z	6
Feed f_z for side milling in steel < 55 HRC	0.05 mm
Helix angle	45 degrees
Corner chamfer angle	90 degrees
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	H
Cutting width a_e for milling operation	0.05×D for side milling
Through-coolant	no
Colour ring	red
Type of product	End mill

Services

Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 16 mm	SZ2025 16
Shank grinding Type HB	129100 HB
Shank recess Type FRST	209900 FRST