

Garant

GARANT Master Alu SlotMachine solid carbide roughing end mill HPC, DLC, Ø e8 DC: 4 mm



Order data

Order number	205250 4
GTIN	4062406122195
Item class	11X

Description

Version:

For roughing.
Special profile for machining non-ferrous metals.

Advantage:

Optimised flute form, eccentric relief ground, generous chip spaces.

Up to $2 \times D$ into solid material at very high feed rates and smooth cutting action.

Ramping capability up to 45° .

Very high feed rates when plunging vertically, thanks to **special plunging geometry**.

Tolerance nominal \varnothing : e8

No. of teeth Z: 3

Helix angle: 35 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 3

Flute length L_c : 8 mm

Overall length L: 57 mm

Shank $\varnothing D_s$: 6 mm

Corner rounding r_v : 0.1 mm

Feed f_z for slot milling in short-chipping aluminium: 0.04 mm

Technical description

Balance quality with shank	G 2.5 with HA
Shank $\varnothing D_s$	6 mm

Flute length L_c	8 mm
Overall length L	57 mm
Helix angle	35 degrees
No. of teeth Z	3
Feed f_z for slot milling in short-chipping aluminium	0.04 mm
Cutting edge $\varnothing D_c$	4 mm
Tolerance nominal \varnothing	e8
Shank	DIN 6535 HA to h6
Direction of infeed	horizontal, oblique and vertical
Feed f_z for side milling in short-chipping aluminium	0.06 mm
Corner rounding r_v	0.1 mm
Series	GARANT Master Alu
Coating	DLC
Tool material	Solid carbide
Standard	DIN 6527
Milling profile	WR
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	0.4×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	HPC
Colour ring	yellow
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------