Garant

GARANT Master Alu SlotMachine solid carbide roughing end mill with through-coolant HPC, DLC, \emptyset e8 DC: 20 mm



Order data

Order number	205256 20
GTIN	4062406277017
Item class	11X

Description

Version:

For roughing.

Special profile for machining non-ferrous metals.

Improved chip evacuation due to central through-coolant. Due to the patented geometry also suitable for boring.

Advantage:

Optimised flute form, eccentric relief ground, generous chip spaces.

Up to $2 \times D$ into solid material at very high feed rates and smooth cutting action. Ramping capability up to 45° . Very high feed rates when plunging vertically, thanks to **special plunging geometry**. Tolerance nominal Ø: e8 No. of teeth Z: 4 Helix angle: 35 degrees Direction of infeed: horizontal, oblique and vertical Shank: DIN 6535 HB to h6 Balance quality with shank: G 2.5 with HB No. of teeth Z: 4 Flute length L_c: 41 mm Overhang length L₁ incl. recess: 52 mm Recess Ø D₁: 19 mm Overall length L: 104 mm Shank Ø D_s: 20 mm

Technical description

roup 🖈 Hoffmann Group

Data sheet

No. of teeth Z	4
Tolerance nominal Ø	e8
Feed f_z for side milling in short-chipping aluminium	0.28 mm
Direction of infeed	horizontal, oblique and vertical
Helix angle	35 degrees
Cutting edge $Ø D_c$	20 mm
Shank Ø D _s	20 mm
Shank	DIN 6535 HB to h6
Overall length L	104 mm
Balance quality with shank	G 2.5 with HB
Recess Ø D ₁	19 mm
Overhang length L ₁ incl. recess	52 mm
Flute length L_c	41 mm
Feed f_z for slot milling in short-chipping aluminium	0.25 mm
Corner rounding r _v	0.5 mm
Series	GARANT Master Alu
Coating	DLC
Tool material	Solid carbide
Standard	DIN 6527
Milling profile	WR
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	yes
Machining strategy	HPC
Colour ring	yellow
Type of product	End mill

Services

© Hoffmann GmbH Qualitätswerkzeuge

Shank grinding Type HB

129100 HB