

Garant

GARANT Master Alu SlotMachine solid carbide roughing end mill with through-coolant HPC, DLC, Ø e8 DC: 8 mm



Order data

Order number	205256 8
GTIN	4062406276959
Item class	11X

Description

Version:

For roughing.

Special profile for machining non-ferrous metals.

Improved chip evacuation due to central through-coolant. Due to the patented geometry also suitable for boring.

Advantage:

Optimised flute form, eccentric relief ground, generous chip spaces.

Up to $2 \times D$ into solid material at very high feed rates and smooth cutting action.

Ramping capability up to 45° .

Very high feed rates when plunging vertically, thanks to **special plunging geometry**.

Tolerance nominal Ø: e8

No. of teeth Z: 3

Helix angle: 35 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

Balance quality with shank: G 2.5 with HB

No. of teeth Z: 3

Flute length L_c : 19 mm

Overhang length L_1 incl. recess: 25 mm

Recess Ø D_1 : 7.5 mm

Overall length L: 63 mm

Shank Ø D_s : 8 mm

Technical description

Helix angle	35 degrees
Cutting edge $\varnothing D_c$	8 mm
Overall length L	63 mm
Shank	DIN 6535 HB to h6
Feed f_z for slot milling in short-chipping aluminium	0.1 mm
Flute length L_c	19 mm
Overhang length L_1 incl. recess	25 mm
No. of teeth Z	3
Feed f_z for side milling in short-chipping aluminium	0.12 mm
Balance quality with shank	G 2.5 with HB
Shank $\varnothing D_s$	8 mm
Direction of infeed	horizontal, oblique and vertical
Recess $\varnothing D_1$	7.5 mm
Tolerance nominal \varnothing	e8
Corner rounding r_v	0.2 mm
Series	GARANT Master Alu
Coating	DLC
Tool material	Solid carbide
Standard	DIN 6527
Milling profile	WR
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Through-coolant	yes
Machining strategy	HPC
Colour ring	yellow
Type of product	End mill

Services

Shank grinding Type HB

129100 HB