

Garant**GARANT Master Alu SlotMachine solid carbide roughing end mill HPC, DLC, Ø e8 DC: 6 mm****Order data**

Order number	205265 6
GTIN	4062406122539
Item class	11X

Description**Version:**

For roughing.

Special profile for machining non-ferrous metals.

Advantage:

Optimised flute form, eccentric relief ground, generous chip spaces.

Up to $2 \times D$ into solid material at very high feed rates and smooth cutting action.

Ramping capability up to 45° .

Very high feed rates when plunging vertically, thanks to **special plunging geometry**.

Tolerance nominal Ø: e8

No. of teeth Z: 3

Helix angle: 35 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 3

Flute length L_c : 18 mm

Overhang length L_1 incl. recess: 24 mm

Recess Ø D_1 : 5.5 mm

Overall length L: 62 mm

Shank Ø D_s : 6 mm

Technical description

Recess Ø D_1	5.5 mm
Cutting edge Ø D_c	6 mm

Shank Ø D _s	6 mm
Flute length L _c	18 mm
Overhang length L ₁ incl. recess	24 mm
Shank	DIN 6535 HA to h6
Helix angle	35 degrees
Overall length L	62 mm
No. of teeth Z	3
Feed f _z for slot milling in short-chipping aluminium	0.08 mm
Direction of infeed	horizontal, oblique and vertical
Feed f _z for side milling in short-chipping aluminium	0.1 mm
Balance quality with shank	G 2.5 with HA
Tolerance nominal Ø	e8
Corner rounding r _v	0.2 mm
Series	GARANT Master Alu
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Milling profile	WR
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a _e for milling operation	0.5×D for side milling
Cutting width a _e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Machining strategy	HPC
Colour ring	yellow
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------

