

Garant
GARANT Master Alu SlotMachine solid carbide roughing end mill HPC, DLC, Ø e8 DC: 10 mm

Order data

Order number	205275 10
GTIN	4062406381332
Item class	11X

Description
Version:

For roughing.

Special profile for machining non-ferrous metals. Significant reduction in the chip volume due to targeted chip fragmentation using the **special cutter geometry**.

Problem-solver for TPC machining. Ideal for automated production as the risk of chip accumulations in the machine is largely prevented.

Note:

Please use tools with HB drive flats for particularly demanding roughing machining tasks. Can be ordered in the Hoffmann Group's e-shop.

For **HB shanks** use order **no. 205277**.

HB shanks are available at the same price as HA.

h_{max} : The values stated in the table are maximum values.

ae_{max} is $0.1 \times D$ for TPC machining.

Tolerance nominal Ø: e8

No. of teeth Z: 3

Helix angle: 35 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 3

Flute length L_c : 51 mm

Overhang length L_1 incl. recess: 60 mm

Recess Ø D_1 : 9.5 mm

Overall length L: 104 mm

Shank Ø D_s : 10 mm

Technical description

No. of teeth Z	3
Corner rounding r_v	0.32 mm
Average chip thickness h_{max} for TPC milling in short-chipping aluminium	0.06 mm
Tolerance nominal \varnothing	e8
Balance quality with shank	G 2.5 with HA
Shank	DIN 6535 HA to h6
Shank $\varnothing D_s$	10 mm
Recess $\varnothing D_1$	9.5 mm
Flute length L_c	51 mm
Overhang length L_1 incl. recess	60 mm
Overall length L	104 mm
Cutting edge $\varnothing D_c$	10 mm
Direction of infeed	horizontal, oblique and vertical
Helix angle	35 degrees
Series	GARANT Master Alu
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Milling profile	WR
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	$0.1 \times D$
Through-coolant	no
Machining strategy	HPC
Colour ring	yellow
Type of product	End mill

