

## Garant

### GARANT Master Alu SlotMachine solid carbide roughing end mill HPC, DLC, Ø e8 DC: 12 mm



#### Order data

Order number	205277 12
GTIN	4062406585846
Item class	11X

#### Description

##### Version:

For roughing.

Special profile for machining non-ferrous metals. Significant reduction in the chip volume due to targeted chip fragmentation using the **special cutter geometry**.

**Problem-solver for TPC machining.** Ideal for automated production as the risk of chip accumulations in the machine is largely prevented.

##### Note:

Please use tools with HB drive flats for particularly demanding roughing machining tasks. Can be ordered in the Hoffmann Group's e-shop.

$h_{max}$ : The values stated in the table are maximum values.

$ae_{max}$  is  $0.1 \times D$  for TPC machining.

Tolerance nominal Ø: e8

No. of teeth Z: 3

Helix angle: 35 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

Balance quality with shank: G 2.5 with HB

No. of teeth Z: 3

Flute length  $L_c$ : 61 mm

Overhang length  $L_1$  incl. recess: 72 mm

Recess Ø  $D_1$ : 11 mm

Overall length L: 120 mm

Shank Ø  $D_s$ : 12 mm

#### Technical description

Direction of infeed	horizontal, oblique and vertical
Flute length $L_c$	61 mm
Shank $\varnothing D_s$	12 mm
Cutting edge $\varnothing D_c$	12 mm
Balance quality with shank	G 2.5 with HB
Average chip thickness $h_{max}$ for TPC milling in short-chipping aluminium	0.072 mm
Tolerance nominal $\varnothing$	e8
Overall length L	120 mm
Recess $\varnothing D_1$	11 mm
Overhang length $L_1$ incl. recess	72 mm
Helix angle	35 degrees
No. of teeth Z	3
Corner rounding $r_v$	0.32 mm
Shank	DIN 6535 HB to h6
Series	GARANT Master Alu
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Milling profile	WR
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width $a_e$ for milling operation	$0.1 \times D$
Through-coolant	no
Machining strategy	HPC
Colour ring	yellow
Type of product	End mill

