


Garant

GARANT Master Alu SlotMachine solid carbide roughing end mill HPC, DLC, Ø e8 DC: 6 mm



Order data

Order number	205277 6
GTIN	4062406585815
Item class	11X

Description

Version:

For roughing.

Special profile for machining non-ferrous metals. Significant reduction in the chip volume due to targeted chip fragmentation using the **special cutter geometry**.

Problem-solver for TPC machining. Ideal for automated production as the risk of chip accumulations in the machine is largely prevented.

Note:

Please use tools with HB drive flats for particularly demanding roughing machining tasks. Can be ordered in the Hoffmann Group's e-shop.

h_{max} : The values stated in the table are maximum values.

ae_{max} is $0.1 \times D$ for TPC machining.

Tolerance nominal Ø: e8

No. of teeth Z: 3

Helix angle: 35 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

Balance quality with shank: G 2.5 with HB

No. of teeth Z: 3

Flute length L_c : 31 mm

Overhang length L_1 incl. recess: 36 mm

Recess Ø D_1 : 5.7 mm

Overall length L: 75 mm

Shank Ø D_s : 6 mm

Technical description

No. of teeth Z	3
Cutting edge $\varnothing D_c$	6 mm
Shank $\varnothing D_s$	6 mm
Flute length L_c	31 mm
Overhang length L_1 incl. recess	36 mm
Helix angle	35 degrees
Balance quality with shank	G 2.5 with HB
Shank	DIN 6535 HB to h6
Overall length L	75 mm
Tolerance nominal \varnothing	e8
Recess $\varnothing D_1$	5.7 mm
Corner rounding r_v	0.2 mm
Average chip thickness h_{max} for TPC milling in short-chipping aluminium	0.036 mm
Direction of infeed	horizontal, oblique and vertical
Series	GARANT Master Alu
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Milling profile	WR
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	$0.1 \times D$
Through-coolant	no
Machining strategy	HPC
Colour ring	yellow
Type of product	End mill

