

Garant
Solid carbide roughing slot drill, DLC, Ø d11 DC: 6 mm

Order data

Order number	205331 6
GTIN	4045197767202
Item class	11X

Description
Version:
Dimensions similar to DIN 6527.
Knuckle form profile.
Special profile for machining non-ferrous metals.

 With the latest generation of **DLC coating sp²**.

Through-coolant: no

Tolerance nominal Ø: d11

No. of teeth Z: 3

Helix angle: 30 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HA to h6

No. of teeth Z: 3

 Flute length L_c: 13 mm

 Overhang length L₁ incl. recess: 21 mm

 Recess Ø D₁: 5.8 mm

Overall length L: 57 mm

 Shank Ø D_s: 6 mm

Technical description

Direction of infeed	horizontal, oblique and vertical
Overall length L	57 mm
Overhang length L ₁ incl. recess	21 mm
Shank Ø D _s	6 mm
Cutting edge Ø D _c	6 mm

Corner chamfer width at 45°	0.35 mm
Feed f_z for side milling in short-chipping aluminium	0.08 mm
Flute length L_c	13 mm
No. of teeth Z	3
Tolerance nominal \varnothing	d11
Shank	DIN 6535 HA to h6
Feed f_z for slot milling in short-chipping aluminium	0.06 mm
Recess $\varnothing D_1$	5.8 mm
Helix angle	30 degrees
Corner chamfer angle	45 degrees
Coating	DLC
Tool material	solid carbide
Standard	Manufacturer's standard
Milling profile	WR
Cutting width a_e for milling operation	0.5×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Through-coolant	no
Colour ring	yellow
Type of product	End mill

Services

Shank clamping flats for shrink-fit chucks, with retainer function Shank \varnothing tool 12 mm	SZ2025 12
Shank grinding Type HB	129100 HB