

Garant
GARANT Master Steel SlotMachine solid carbide roughing end mill HPC / TPC, TiAlN, Ø d11 DC: 16 mm

Order data

Order number	205557 16
GTIN	4062406377069
Item class	11X

Description
Version:

With a new-type knurled profile, optimised for higher feed rates. Improved cutting edge protection thanks to slight edge honing. Tremendous bending strength due to the use of ultra-fine grain substrate.

Advantage:

The tool geometry produces particularly tightly rolled swarf that is discharged via flat chip breaker recesses. As a result, the tool maintains an extremely stable core. Plunge angle of up to 10° possible thanks to generous recess on the front face.

Application:

For roughing machining.

Problem-solver for TPC machining.

Tolerance nominal Ø: d11

No. of teeth Z: 5

Helix angle: 42 degrees

Direction of infeed: horizontal, oblique and vertical

Shank: DIN 6535 HB to h6

No. of teeth Z: 5

Flute length L_c : 80 mm

Overall length L: 136 mm

Shank Ø D_s : 16 mm

Corner chamfer width at 45°: 0.8 mm

Feed f_z for side milling in steel < 900 N/mm²: 0.09 mm

Technical description

Cutting edge Ø D_c	16 mm
----------------------	-------

Feed f_z for side milling in steel $< 900 \text{ N/mm}^2$	0.09 mm
Shank $\varnothing D_s$	16 mm
Flute length L_c	80 mm
Corner chamfer width at 45°	0.8 mm
No. of teeth Z	5
Tolerance nominal $\varnothing$	d11
Direction of infeed	horizontal, oblique and vertical
Helix angle	42 degrees
Corner chamfer angle	45 degrees
Overall length L	136 mm
Shank	DIN 6535 HB to h6
Series	GARANT Master Steel
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Milling profile	NR
Spacing of the cutters	unequal spacing
Cutting width a_e for milling operation	$0.2 \times D$ for side milling
Through-coolant	no
Machining strategy	TPC
Machining strategy	HPC
Colour ring	green
Type of product	End mill