

Garant

GARANT Master Alu solid carbide torus cutter HPC, DLC, Ø h6 DC / RS1: 16/2,0 mm



Order data

Order number	206264 16/2,0
GTIN	4062406398675
Item class	11X

Description

Version:

Eccentric relief ground, additionally polish ground in the flutes for outstanding chip evacuation in long-chipping non-ferrous materials.

Very high feed rates when plunging vertically. Ramping capability up to 45°.

Tolerances:

· Corner radius

RS₁ = 0.5 tolerance ±0.02.

RS₁ > 0.5 – 1.5 tolerance ±0.03.

RS₁ > 1.5 tolerance ±0.05.

Application:

Particularly suitable for finishing work.

No. of teeth Z: 5

Shank: DIN 6535 HA to h6

Balance quality with shank: G 2.5 with HA

No. of teeth Z: 5

Flute length L_c: 65 mm

Corner radius R₁: 2 mm

Overhang length L₁ incl. recess: 80 mm

Recess Ø D₁: 15 mm

Overall length L: 125 mm

Technical description

Feed f _z for side milling in short-chipping aluminium	0.07 mm
Recess Ø D ₁	15 mm

Balance quality with shank	G 2.5 with HA
Shank $\varnothing D_s$	16 mm
Cutting edge $\varnothing D_c$	16 mm
Overhang length L_1 incl. recess	80 mm
No. of teeth Z	5
Corner radius R_1	2 mm
Overall length L	125 mm
Flute length L_c	65 mm
Shank	DIN 6535 HA to h6
Series	GARANT Master Alu
Coating	DLC
Tool material	Solid carbide
Standard	DIN 6527
Tolerance nominal \varnothing	e8
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Through-coolant	no
Machining strategy	HPC
Colour ring	yellow
Type of product	End mill