

Garant
GARANT Master Titan solid carbide end torus cutter HPC, TiAlN, Ø h9 DC: 2 mm

Order data

Order number	206286 2
GTIN	4045197991317
Item class	11Z

Description
Version:

Tolerance: Corner radius $R_1 = \pm 0.01$ mm.

Special centre cutting edge geometry for traverse milling at very high feed rates.

Application:

For copy and traverse milling of titanium under HPC conditions.

Using special milling strategies **very high rates of metal removal can be achieved.**

Note:

Regrinding not recommended.

No. of teeth Z: 2

No. of teeth Z: 2

Dimension $a_{p\max}$ transverse: 0.15 mm

Programming radius: 0.3 mm

Flute length L_c : 1.5 mm

Overhang length L_1 incl. recess: 13 mm

Recess Ø D_1 : 1.7 mm

Technical description

Overall length L	54 mm
Recess Ø D_1	1.7 mm
Flute length L_c	1.5 mm
No. of teeth Z	2
Cutting edge Ø D_c	2 mm

Shank Ø D _s	6 mm
Overhang length L ₁ incl. recess	13 mm
Dimension a _{p max} transverse	0.15 mm
Feed f _z for copy milling in titanium > 850 N/mm ²	0.018 mm
Programming radius	0.3 mm
Setting angle κ	11 degrees
Series	GARANT Master Titan
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal Ø	h9
Helix angle	15 degrees
Direction of infeed	horizontal, oblique and vertical
Cutting width a _e for milling operation	0.05×D for copy milling
Shank	DIN 6535 HA to h6
Through-coolant	no
Machining strategy	HPC
Colour ring	pink
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------