

## Garant

### GARANT Master Steel solid carbide torus cutter HPC, TiAlN, Ø e8 DC / R1: 2/0,2 mm



#### Order data

Order number	206333 2/0,2
GTIN	4062406276157
Item class	11X

#### Description

##### Version:

HPC milling cutter with **newly developed high-performance coating**. For **outstanding tool life** and **optimum metal removal rates** in a range of materials.

With **double relief ground side clearance angle**.

Tolerance: Corner radius  $R_1$

Radius size 0.1 mm – 1 mm:  $R_1 = \pm 0.003$  mm.

Radius size > 1.0 mm – 1 mm :  $R_1 = \pm 0.005$  mm.

##### Advantage:

Optimised flute form, eccentric relief ground, wide chip space.

##### Application:

Especially for **high speed machining** in **mould and tool making** for **copy milling**. Excellent results for **dry milling**.

No. of teeth Z: 4

Helix angle: 30 degrees

Shank: DIN 6535 HA to h6

No. of teeth Z: 4

Flute length  $L_c$ : 2.5 mm

Corner radius  $R_1$ : 0.2 mm

Overhang length  $L_1$  incl. recess: 12 mm

minimum shank recess dia.  $D_5$ : 1.8 mm

maximum shank recess dia.  $D_6$ : 1.95 mm

#### Technical description

Feed $f_z$ for side milling in steel < 1100 N/mm <sup>2</sup>	0.008 mm
---	----------

Overall length L	50 mm
Helix angle	30 degrees
Flute length $L_c$	2.5 mm
Shank $\varnothing D_s$	3 mm
Corner radius $R_1$	0.2 mm
Cutting edge $\varnothing D_c$	2 mm
Feed $f_z$ for copy milling in steel $< 1100 \text{ N/mm}^2$	0.01 mm
No. of teeth Z	4
Overhang length $L_1$ incl. recess	12 mm
Shank	DIN 6535 HA to h6
minimum shank recess dia. $D_5$	1.8 mm
maximum shank recess dia. $D_6$	1.95 mm
Series	GARANT Master Steel
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	H
Tolerance nominal $\varnothing$	e8
Direction of infeed	horizontal, oblique and vertical
Cutting width $a_e$ for milling operation	$0.03 \times D$ for copy milling
Cutting width $a_e$ for milling operation	$0.2 \times D$ for side milling
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill