

Garant

GARANT Master Titan solid carbide torus cutter HPC, TiAlN, Ø DC / R1: 12/0,5 mm



Order data

Order number	206364 12/0,5
GTIN	4045197991904
Item class	11Z

Description

Version:

Tolerance: Corner radius $R_1 = \pm 0.005$ mm.

Application:

For milling **titanium and titanium alloys**; with very smooth cutting action for optimum tool life and top metal removal rate.

No. of teeth Z: 4

Helix angle: 40 degrees

Shank: DIN 6535 HA to h6

No. of teeth Z: 4

Flute length L_c : 26 mm

Corner radius R_1 : 0.5 mm

Overhang length L_1 incl. recess: 38 mm

Recess Ø D_1 : 11.6 mm

Overall length L: 83 mm

Technical description

Overall length L	83 mm
Feed f_z for side milling in titanium > 850 N/mm ²	0.05 mm
Cutting edge Ø D_c	12 mm
Feed f_z for copy milling in titanium > 850 N/mm ²	0.07 mm
No. of teeth Z	4
Helix angle	40 degrees

Correction factor for v_c	1.5
Recess $\varnothing D_1$	11.6 mm
Overhang length L_1 incl. recess	38 mm
Flute length L_c	26 mm
Shank	DIN 6535 HA to h6
Corner radius R_1	0.5 mm
Shank $\varnothing D_s$	12 mm
Series	GARANT Master Titan
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Tolerance nominal \varnothing	e8
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	0.3×D for side milling
Cutting width a_e for milling operation	0.5×D for side milling
Through-coolant	no
Machining strategy	HPC
Shank tolerance	h6
Colour ring	pink
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------