

Garant
GARANT Master Titan solid carbide torus cutter HPC, TiAlN, Ø DC / R1: 12/2,5 mm

Order data

Order number	206364 12/2,5
GTIN	4045197991935
Item class	11Z

Description
Version:

Tolerance: Corner radius $R_1 = \pm 0.005 \text{ mm}$.

Application:

For milling **titanium and titanium alloys**; with very smooth cutting action for optimum tool life and top metal removal rate.

No. of teeth Z: 4

Helix angle: 40 degrees

Shank: DIN 6535 HA to h6

No. of teeth Z: 4

Flute length L_c : 26 mm

Corner radius R_1 : 2.5 mm

Overhang length L_1 incl. recess: 38 mm

Recess Ø D_1 : 11.6 mm

Overall length L: 83 mm

Technical description

No. of teeth Z	4
Cutting edge Ø D_c	12 mm
Flute length L_c	26 mm
Shank Ø D_s	12 mm
Overall length L	83 mm
Feed f_z for side milling in titanium $> 850 \text{ N/mm}^2$	0.05 mm

Recess $\varnothing D_1$	11.6 mm
Overhang length L_1 incl. recess	38 mm
Feed f_z for copy milling in titanium $> 850 \text{ N/mm}^2$	0.07 mm
Helix angle	40 degrees
Correction factor for v_c	1.5
Corner radius R_1	2.5 mm
Shank	DIN 6535 HA to h6
Series	GARANT Master Titan
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Tolerance nominal $\varnothing$	e8
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	$0.3 \times D$ for side milling
Cutting width a_e for milling operation	$0.5 \times D$ for side milling
Through-coolant	no
Machining strategy	HPC
Shank tolerance	h6
Colour ring	pink
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------