

Garant
GARANT Master Titan solid carbide torus cutter HPC, TiAlN, Ø DC / R1: 6/1,0 mm

Order data

Order number	206364 6/1,0
GTIN	4045197991843
Item class	11Z

Description
Version:

Tolerance: Corner radius $R_1 = \pm 0.005 \text{ mm}$.

Application:

For milling **titanium and titanium alloys**; with very smooth cutting action for optimum tool life and top metal removal rate.

No. of teeth Z: 4

Helix angle: 40 degrees

Shank: DIN 6535 HA to h6

No. of teeth Z: 4

Flute length L_c : 13 mm

Corner radius R_1 : 1 mm

Overhang length L_1 incl. recess: 20 mm

Recess Ø D_1 : 5.8 mm

Overall length L: 57 mm

Technical description

Helix angle	40 degrees
Corner radius R_1	1 mm
No. of teeth Z	4
Flute length L_c	13 mm
Overall length L	57 mm
Correction factor for v_c	1.5

Overhang length L_1 incl. recess	20 mm
Recess $\varnothing D_1$	5.8 mm
Feed f_z for side milling in titanium $> 850 \text{ N/mm}^2$	0.026 mm
Shank $\varnothing D_s$	6 mm
Feed f_z for copy milling in titanium $> 850 \text{ N/mm}^2$	0.03 mm
Cutting edge $\varnothing D_c$	6 mm
Shank	DIN 6535 HA to h6
Series	GARANT Master Titan
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Tolerance nominal $\varnothing$	e8
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	$0.3 \times D$ for side milling
Cutting width a_e for milling operation	$0.5 \times D$ for side milling
Through-coolant	no
Machining strategy	HPC
Shank tolerance	h6
Colour ring	pink
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------