

Garant

GARANT Master Titan solid carbide torus cutter HPC, TiAlN, Ø DC / R1: 8/1,0 mm



Order data

Order number	206364 8/1,0
GTIN	4045197991867
Item class	11Z

Description

Version:

Tolerance: Corner radius $R_1 = \pm 0.005$ mm.

Application:

For milling **titanium and titanium alloys**; with very smooth cutting action for optimum tool life and top metal removal rate.

No. of teeth Z: 4

Helix angle: 40 degrees

Shank: DIN 6535 HA to h6

No. of teeth Z: 4

Flute length L_c : 19 mm

Corner radius R_1 : 1 mm

Overhang length L_1 incl. recess: 25 mm

Recess Ø D_1 : 7.7 mm

Overall length L: 63 mm

Technical description

Cutting edge Ø D_c	8 mm
Feed f_z for side milling in titanium > 850 N/mm ²	0.034 mm
Corner radius R_1	1 mm
Helix angle	40 degrees
Overall length L	63 mm
Correction factor for v_c	1.5

No. of teeth Z	4
Feed f_z for copy milling in titanium $> 850 \text{ N/mm}^2$	0.046 mm
Flute length L_c	19 mm
Recess $\varnothing D_1$	7.7 mm
Overhang length L_1 incl. recess	25 mm
Shank	DIN 6535 HA to h6
Shank $\varnothing D_s$	8 mm
Series	GARANT Master Titan
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Tolerance nominal \varnothing	e8
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	0.3×D for side milling
Cutting width a_e for milling operation	0.5×D for side milling
Through-coolant	no
Machining strategy	HPC
Shank tolerance	h6
Colour ring	pink
Type of product	End mill

Services

Shank grinding Type HB

129100 HB