

Garant
GARANT Master Ni-Based torus cutter HPC, TiAlN, Ø DC / R1: 4/0,5 mm

Order data

Order number	206371 4/0,5
GTIN	4062406565237
Item class	11Z

Description
Version:

Innovative substrate specially for machining **nickel-based alloys**. Newly developed coating.

Application:

For milling **nickel-based alloys with high red hardness**.

No. of teeth Z: 4

Helix angle: 35 degrees

Shank: DIN 6535 HB to h6

No. of teeth Z: 4

Flute length L_c : 11 mm

Corner radius R_1 : 0.5 mm

Overhang length L_1 incl. recess: 16 mm

Recess Ø D_1 : 3.8 mm

Overall length L: 57 mm

Technical description

Shank	DIN 6535 HB to h6
Overhang length L_1 incl. recess	16 mm
Recess Ø D_1	3.8 mm
Helix angle	35 degrees
Flute length L_c	11 mm
Shank Ø D_s	6 mm
Overall length L	57 mm

Cutting edge $\varnothing D_c$	4 mm
Corner radius R_1	0.5 mm
No. of teeth Z	4
Feed f_z for side milling in Inconel®	0.018 mm
Series	GARANT Master Ni-Based
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Tolerance nominal $\varnothing$	f8
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	$0.3 \times D$ for side milling
Cutting width a_e for milling operation	$0.05 \times D$ for copy milling
Through-coolant	no
Machining strategy	HPC
Shank tolerance	h6
Colour ring	pink
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------