

Garant
GARANT Master Ni-Based torus cutter HPC, TiAlN, Ø f8 DC / R1: 10/1,0 mm

Order data

Order number	206373 10/1,0
GTIN	4062406565435
Item class	11Z

Description
Version:

Innovative substrate specially for machining **nickel-based alloys**. Newly developed coating.

Application:

For milling **nickel-based alloys with high red hardness**.

For finishing operations.

No. of teeth Z: 6

Helix angle: 50 degrees

Shank: DIN 6535 HA to h6

No. of teeth Z: 6

Flute length L_c : 31 mm

Corner radius R_1 : 1 mm

Overhang length L_1 incl. recess: 41 mm

Recess Ø D_1 : 9.8 mm

Overall length L: 83 mm

Technical description

Overall length L	83 mm
Overhang length L_1 incl. recess	41 mm
Shank Ø D_s	10 mm
Recess Ø D_1	9.8 mm
Corner radius R_1	1 mm
Flute length L_c	31 mm
No. of teeth Z	6

Shank	DIN 6535 HA to h6
Helix angle	50 degrees
Cutting edge $\varnothing D_c$	10 mm
Feed f_z for side milling in Inconel®	0.04 mm
Series	GARANT Master Titan
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 6527
Type	N
Tolerance nominal \varnothing	e8
Helix angle characteristic	unequal spacing
Spacing of the cutters	unequal spacing
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Cutting width a_e for milling operation	$0.05 \times D$ for copy milling
Through-coolant	no
Machining strategy	HPC
Shank tolerance	h6
Colour ring	pink
Type of product	End mill