

Garant
Solid carbide copy slot drill, DLC, Ø DC × L1: 0,8X2 mm


Order data

Order number	207025 0,8X2
GTIN	4062406386818
Item class	11X

Description

Version:

With **advanced DLC sp² coating**. For the **highest demands regarding performance and precision in aluminium materials**. **Extremely tight tolerances** ensure maximum accuracy. Double-relief ground with 2 chamfers.

Tolerances:

- **Corner radius: Radius contour = 0 / -0.005 mm.**
- **Neck Ø: D₁ = 0 / -0.01 mm.**

Recess angle α = 16°.

Extra-sturdy shank to reduce the tendency to vibrate.

Note:

At greater tool overhang lengths, use a reduced value for a_p!
values for:

copying: a_p = 0.25 × D × a_{p korr}

To calculate the feed rate vf please use the actual speed of the machine (the maximum possible speed)!

e.g: vf = 18000 [rpm] × fz [mm/Z] × z

No. of teeth Z: 2

Helix angle: 25 degrees

No. of teeth Z: 2

Flute length L_c: 0.64 mm

Corner radius R₁: 0.4 mm

Overhang length L₁ incl. recess: 2 mm

Recess Ø D₁: 0.77 mm

Overall length L: 55 mm

Technical description

Cutting edge $\varnothing D_c$	0.8 mm
Corner radius R_1	0.4 mm
Recess $\varnothing D_1$	0.77 mm
No. of teeth Z	2
Shank $\varnothing D_s$	6 mm
Overhang length L_1 incl. recess	2 mm
Overall length L	55 mm
Feed f_z for copy milling in cast aluminium	0.024 mm
Correction factor $a_{p\text{corr}}$	1
Helix angle	25 degrees
Flute length L_c	0.64 mm
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Tolerance nominal $\varnothing$	0 / -0.005
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	0.05×D for copy milling
Shank	DIN 6535 HA to h5
Through-coolant	no
Colour ring	yellow
Type of product	End mill