

Garant
Solid carbide copy slot drill, DLC, Ø DC × L1: 1X5 mm

Order data

Order number	207025 1X5
GTIN	4062406386849
Item class	11X

Description
Version:

With **advanced DLC sp² coating**. For the **highest demands regarding performance and precision in aluminium materials**. **Extremely tight tolerances** ensure maximum accuracy. Double-relief ground with 2 chamfers.

Tolerances:

- **Corner radius: Radius contour = 0 / -0.005 mm.**
- **Neck Ø: D₁ = 0 / -0.01 mm.**

Recess angle α = 16°.

Extra-sturdy shank to reduce the tendency to vibrate.

Note:

At greater tool overhang lengths, use a reduced value for a_p!
values for:

copying: $a_p = 0.25 \times D \times a_{p\text{ kor}}$

To calculate the feed rate vf please use the actual speed of the machine (the maximum possible speed)!

e.g: $vf = 18000 [\text{rpm}] \times fz [\text{mm/Z}] \times z$

No. of teeth Z: 2

Helix angle: 30 degrees

No. of teeth Z: 2

Flute length L_c: 0.8 mm

Corner radius R₁: 0.5 mm

Overhang length L₁ incl. recess: 5 mm

Recess Ø D₁: 0.96 mm

Overall length L: 55 mm

Technical description

Overall length L	55 mm
Corner radius R ₁	0.5 mm
Correction factor a _{p corr}	1
Overhang length L ₁ incl. recess	5 mm
Helix angle	30 degrees
No. of teeth Z	2
Cutting edge Ø D _c	1 mm
Recess Ø D ₁	0.96 mm
Feed f _z for copy milling in cast aluminium	0.036 mm
Shank Ø D _s	6 mm
Flute length L _c	0.8 mm
Coating	DLC
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	W
Tolerance nominal Ø	0 / -0.005
Direction of infeed	horizontal, oblique and vertical
Cutting width a _e for milling operation	0.05×D for copy milling
Shank	DIN 6535 HA to h5
Through-coolant	no
Colour ring	yellow
Type of product	End mill