


Garant
**GARANT Master Steel solid carbide ball nose slot drill HPC, TiAlN, Ø f8 DC / D
S: 0,25 mm**

Order data

Order number	207242 0,25
GTIN	4062406284725
Item class	11X

Description
Version:
Precision ground for very high accuracy requirements.

Tolerance: Radius contour = ± 0.005 mm.

Improved cutting edge protection thanks to slight edge honing. Tremendous bending strength due to the use of ultra-fine grain substrate.

No. of teeth Z: 2

Helix angle: 28 degrees

No. of teeth Z: 2

Flute length L_c : 0.5 mm

Overall length L: 38 mm

Shank $\varnothing D_s$: 3 mm

Feed f_z for side milling in steel < 900 N/mm²: 0.005 mm

Feed f_z for copy milling in steel < 900 N/mm²: 0.007 mm

Technical description

Feed f_z for copy milling in steel < 900 N/mm ²	0.007 mm
Feed f_z for side milling in steel < 900 N/mm ²	0.005 mm
Shank $\varnothing D_s$	3 mm
Flute length L_c	0.5 mm
No. of teeth Z	2
Overall length L	38 mm

Helix angle	28 degrees
Cutting edge $\varnothing D_c$	0.25 mm
Radius R	0.125 mm
Series	GARANT Master Steel
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal \varnothing	f8
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Cutting width a_e for milling operation	$0.03 \times D$ for copy milling
Shank	DIN 6535 HA to h6
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill