

**Garant**
**GARANT Master Steel solid carbide ball nose slot drill HPC, TiAlN, Ø f8 DC / D S: 3/6 mm**

**Order data**

Order number	207242 3/6
GTIN	4062406284954
Item class	11X

**Description**
**Version:**
**Precision ground for very high accuracy requirements.**

Tolerance: Radius contour =  $\pm 0.005$  mm.

Improved cutting edge protection thanks to slight edge honing. Tremendous bending strength due to the use of ultra-fine grain substrate.

No. of teeth Z: 2

Helix angle: 28 degrees

No. of teeth Z: 2

Flute length  $L_c$ : 5 mm

Overall length L: 54 mm

Shank  $\varnothing D_s$ : 6 mm

Feed  $f_z$  for side milling in steel < 900 N/mm<sup>2</sup>: 0.04 mm

Feed  $f_z$  for copy milling in steel < 900 N/mm<sup>2</sup>: 0.06 mm

**Technical description**

Feed $f_z$ for copy milling in steel < 900 N/mm <sup>2</sup>	0.06 mm
Flute length $L_c$	5 mm
No. of teeth Z	2
Cutting edge $\varnothing D_c$	3 mm
Overall length L	54 mm
Shank $\varnothing D_s$	6 mm

Helix angle	28 degrees
Feed $f_z$ for side milling in steel < 900 N/mm <sup>2</sup>	0.04 mm
Radius R	1.5 mm
Series	GARANT Master Steel
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal $\varnothing$	f8
Direction of infeed	horizontal, oblique and vertical
Cutting width $a_e$ for milling operation	Full slot cutting depth $1 \times D$
Cutting width $a_e$ for milling operation	$0.03 \times D$ for copy milling
Shank	DIN 6535 HA to h6
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill