

**Garant**
**GARANT Master Steel solid carbide ball nose slot drill HPC, TiAlN, Ø f8 DC / D  
S: 10 mm**

**Order data**

|              |               |
|--------------|---------------|
| Order number | 207246 10     |
| GTIN         | 4062406285296 |
| Item class   | 11X           |

**Description**
**Version:**
**Precision ground for very high accuracy requirements.**

Tolerance: Radius contour =  $\pm 0.005$  mm.

Improved cutting edge protection thanks to slight edge honing. Tremendous bending strength due to the use of ultra-fine grain substrate.

No. of teeth Z: 2

Helix angle: 28 degrees

No. of teeth Z: 2

Flute length  $L_c$ : 14 mm

Overall length L: 120 mm

Shank Ø  $D_s$ : 10 mm

Feed  $f_z$  for side milling in steel < 900 N/mm<sup>2</sup>: 0.1 mm

Feed  $f_z$  for copy milling in steel < 900 N/mm<sup>2</sup>: 0.12 mm

**Technical description**

|                                                              |            |
|--------------------------------------------------------------|------------|
| Helix angle                                                  | 28 degrees |
| Cutting edge Ø $D_c$                                         | 10 mm      |
| Shank Ø $D_s$                                                | 10 mm      |
| Feed $f_z$ for side milling in steel < 900 N/mm <sup>2</sup> | 0.1 mm     |
| Flute length $L_c$                                           | 14 mm      |
| No. of teeth Z                                               | 2          |
| Feed $f_z$ for copy milling in steel < 900 N/mm <sup>2</sup> | 0.12 mm    |

|                                           |                                  |
|-------------------------------------------|----------------------------------|
| Overall length L                          | 120 mm                           |
| Radius R                                  | 5 mm                             |
| Series                                    | GARANT Master Steel              |
| Coating                                   | TiAlN                            |
| Tool material                             | Solid carbide                    |
| Standard                                  | Manufacturer's standard          |
| Type                                      | N                                |
| Tolerance nominal Ø                       | f8                               |
| Direction of infeed                       | horizontal, oblique and vertical |
| Cutting width $a_e$ for milling operation | $0.5 \times D$ for side milling  |
| Cutting width $a_e$ for milling operation | $0.03 \times D$ for copy milling |
| Shank                                     | DIN 6535 HA to h6                |
| Through-coolant                           | no                               |
| Machining strategy                        | HPC                              |
| Colour ring                               | green                            |
| Type of product                           | End mill                         |