

**Garant**
**Solid carbide ball nose slot drill HPC, TiAlN, Ø f8 DC / D S: 4 mm**

**Order data**

Order number	207280 4
GTIN	4045197127488
Item class	11X

**Description**
**Version:**
**Precision ground for very high accuracy requirements.**

Tolerance: Radius contour =  $\pm 0.005$  mm.

**Note:**
**Recommended successor product is No. 207244.**

No. of teeth Z: 2

Helix angle: 30 degrees

No. of teeth Z: 2

Flute length  $L_c$ : 8 mm

Overall length L: 75 mm

Shank  $\varnothing D_s$ : 4 mm

Feed  $f_z$  for side milling in steel < 1100 N/mm<sup>2</sup>: 0.032 mm

Feed  $f_z$  for copy milling in steel < 1100 N/mm<sup>2</sup>: 0.037 mm

**Technical description**

Feed $f_z$ for side milling in steel < 1100 N/mm <sup>2</sup>	0.032 mm
Cutting edge $\varnothing D_c$	4 mm
No. of teeth Z	2
Feed $f_z$ for copy milling in steel < 1100 N/mm <sup>2</sup>	0.037 mm
Shank $\varnothing D_s$	4 mm
Overall length L	75 mm
Flute length $L_c$	8 mm

Helix angle	30 degrees
Radius R	2 mm
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	H
Tolerance nominal $\varnothing$	f8
Direction of infeed	horizontal, oblique and vertical
Cutting width $a_e$ for milling operation	0.5×D for side milling
Cutting width $a_e$ for milling operation	0.03×D for copy milling
Shank	DIN 6535 HA to h6
Through-coolant	no
Machining strategy	HPC
Colour ring	without
Type of product	End mill

## Services

Shank recess Type FRST	209900 FRST
------------------------	-------------