

Garant
Diabolo solid carbide copy slot drill, TiAlN, Ø Dc × L1: 1,5X3 mm

Order data

Order number	207377 1,5X3
GTIN	4062406387891
Item class	11X

Description
Version:
GARANT Diabolo:

Special geometry, coating and carbide **for hard machining in the high-performance field.**

Suitable even for **machining electrolytic copper.**

Recess angle $\alpha = 16^\circ$.

Extra-sturdy shank for achieving longer tool life.

Tolerances:

- **Corner radius: Radius contour = 0 / -0.005 mm.**
- **Neck Ø: D₁ = 0 / -0.01 mm.**

Note:

At greater tool overhang lengths, use a reduced value for a_p!
values for:

copying: $a_p = 0.05 \times D \times a_{p, \text{korr}}$

To calculate the feed rate vf please use the actual speed of the machine (the maximum possible speed)! e.g: $vf = 18000 \text{ [rpm]} \times fz \text{ [mm/Z]} \times z$

No. of teeth Z: 2

Helix angle: 30 degrees

No. of teeth Z: 2

Flute length L_c: 1.2 mm

Corner radius R₁: 0.75 mm

Overhang length L₁ incl. recess: 3 mm

Recess Ø D₁: 1.44 mm

Overall length L: 54 mm

Technical description

Overhang length L ₁ incl. recess	3 mm
---	------

Flute length L_c	1.2 mm
Corner radius R_1	0.75 mm
No. of teeth Z	2
Overall length L	54 mm
Shank $\varnothing D_s$	6 mm
Feed f_z for copy milling in steel < 65 HRC	0.022 mm
Helix angle	30 degrees
Cutting edge $\varnothing D_c$	1.5 mm
Recess $\varnothing D_1$	1.44 mm
Correction factor $a_{p,corr}$	1
Series	Diabolo
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	H
Tolerance nominal \varnothing	0 / -0,005
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	0.05×D for copy milling
Shank	DIN 6535 HA to h5
Through-coolant	no
Colour ring	red
Type of product	End mill