

Garant
GARANT Master INOX solid carbide ball nose slot drill HPC, TiAlN, Ø f8 DC / DS: 6 mm

Order data

Order number	207473 6
GTIN	4062406130336
Item class	11X

Description
Version:

HPC milling cutters with **newly developed high-performance coating** for **outstanding service life** and **optimum metal removal rates** in a wide range of stainless steels.

Greater oxidation resistance and **high-temperature hardness**.

Can be used at **high cutting speeds**, particularly suitable even for TOOLOX®.

Tolerance: Radius contour = ± 0.005 mm.

No. of teeth Z: 4

Helix angle: 45 degrees

No. of teeth Z: 4

Flute length L_c : 10 mm

Overall length L: 54 mm

Shank $\varnothing D_s$: 6 mm

Feed f_z for side milling in INOX < 900 N/mm²: 0.017 mm

Feed f_z for copy milling in stainless steel < 900 N/mm²: 0.019 mm

Technical description

No. of teeth Z	4
Flute length L_c	10 mm
Feed f_z for side milling in INOX < 900 N/mm ²	0.017 mm
Helix angle	45 degrees
Shank $\varnothing D_s$	6 mm

Cutting edge $\varnothing D_c$	6 mm
Overall length L	54 mm
Feed f_z for copy milling in stainless steel < 900 N/mm ²	0.019 mm
Radius R	3 mm
Series	GARANT Master INOX
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal \varnothing	f8
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	Full slot cutting depth 1xD
Cutting width a_e for milling operation	0.05xD for side milling
Shank	DIN 6535 HA to h6
Through-coolant	no
Machining strategy	HPC
Colour ring	blue
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
Shank grinding Type HB	129100 HB