

Garant
GARANT Master INOX solid carbide ball nose slot drill HPC, TiAlN, Ø f8 DC / DS: 8 mm

Order data

Order number	207473 8
GTIN	4062406130343
Item class	11X

Description
Version:

HPC milling cutters with **newly developed high-performance coating** for **outstanding service life** and **optimum metal removal rates** in a wide range of stainless steels.

Greater oxidation resistance and **high-temperature hardness**.

Can be used at **high cutting speeds**, particularly suitable even for TOOLOX®.

Tolerance: Radius contour = **±0.005 mm**.

No. of teeth Z: 4

Helix angle: 45 degrees

No. of teeth Z: 4

Flute length L_c: 12 mm

Overall length L: 58 mm

Shank Ø D_s: 8 mm

Feed f_z for side milling in INOX < 900 N/mm²: 0.025 mm

Feed f_z for copy milling in stainless steel < 900 N/mm²: 0.028 mm

Technical description

Feed f _z for copy milling in stainless steel < 900 N/mm ²	0.028 mm
Overall length L	58 mm
Feed f _z for side milling in INOX < 900 N/mm ²	0.025 mm
Shank Ø D _s	8 mm
Helix angle	45 degrees

No. of teeth Z	4
Cutting edge $\varnothing D_c$	8 mm
Flute length L_c	12 mm
Radius R	4 mm
Series	GARANT Master INOX
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal $\varnothing$	f8
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	Full slot cutting depth $1 \times D$
Cutting width a_e for milling operation	$0.05 \times D$ for side milling
Shank	DIN 6535 HA to h6
Through-coolant	no
Machining strategy	HPC
Colour ring	blue
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
Shank grinding Type HB	129100 HB