

Garant
GARANT Master INOX solid carbide ball nose slot drill HPC, TiAlN, Ø f8 DC / DS: 4 mm

Order data

Order number	207474 4
GTIN	4062406130435
Item class	11X

Description
Version:

HPC milling cutters with **newly developed high-performance coating** for **outstanding service life** and **optimum metal removal rates** in a wide range of stainless steels.

Greater oxidation resistance and **high-temperature hardness**.

Can be used at **high cutting speeds**, particularly suitable even for TOOLOX®.

Tolerance: Radius contour = **±0.005 mm**.

No. of teeth Z: 4

Helix angle: 45 degrees

No. of teeth Z: 4

Flute length L_c: 8 mm

Overall length L: 80 mm

Shank Ø D_s: 4 mm

Feed f_z for side milling in INOX < 900 N/mm²: 0.012 mm

Feed f_z for copy milling in stainless steel < 900 N/mm²: 0.013 mm

Technical description

Overall length L	80 mm
Flute length L _c	8 mm
Cutting edge Ø D _c	4 mm
Feed f _z for copy milling in stainless steel < 900 N/mm ²	0.013 mm
No. of teeth Z	4
Helix angle	45 degrees

Feed f_z for side milling in INOX < 900 N/mm ²	0.012 mm
Shank Ø D_s	4 mm
Radius R	2 mm
Series	GARANT Master INOX
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal Ø	f8
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	0.5×D for side milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Shank	DIN 6535 HA to h6
Through-coolant	no
Machining strategy	HPC
Colour ring	blue
Type of product	End mill

Services

Shank recess Type FRST	209900 FRST
------------------------	-------------