

Garant
GARANT Master Titan solid carbide ball nose slot drill HPC, TiAlN, Ø f8 DC / DS: 5 mm

Order data

Order number	207482 5
GTIN	4045197989598
Item class	11Z

Description
Version:

Special geometry for machining **titanium and titanium alloys**.

4 centre cutting edges to the centre.

Therefore can be used as a **true 4-edge cutter** at all depths of cut.

Tolerance: Radius contour = ± 0.005 mm.

Note:

Regrinding not recommended.

No. of teeth Z: 4

Helix angle: 45 degrees

No. of teeth Z: 4

Flute length L_c : 9 mm

Overall length L: 54 mm

Shank $\varnothing D_s$: 6 mm

Feed f_z for side milling in titanium > 850 N/mm²: 0.02 mm

Feed f_z for copy milling in titanium > 850 N/mm²: 0.024 mm

Technical description

Flute length L_c	9 mm
Correction factor for v_c	1.25
Shank $\varnothing D_s$	6 mm
Feed f_z for side milling in titanium > 850 N/mm ²	0.02 mm
Feed f_z for copy milling in titanium > 850 N/mm ²	0.024 mm

Overall length L	54 mm
Helix angle	45 degrees
No. of teeth Z	4
Cutting edge $\varnothing D_c$	5 mm
Radius R	2.5 mm
Series	GARANT Master Titan
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal \varnothing	f8
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	0.5×D for side milling
Cutting width a_e for milling operation	0.05×D for side milling
Shank	DIN 6535 HA to h6
Through-coolant	no
Machining strategy	HPC
Colour ring	pink
Type of product	End mill

Services

Shank grinding Type HB	129100 HB
------------------------	-----------