

Garant
GARANT Master Steel solid carbide ball nose slot drill HPC, TiAlN, Ø f8 DC: 14 mm

Order data

Order number	207490 14
GTIN	4062406285395
Item class	11X

Description
Version:
Precision ground for very high accuracy requirements.

Tolerance: Radius contour = ± 0.005 mm.

Improved cutting edge protection thanks to slight edge honing. Tremendous bending strength due to the use of ultra-fine grain substrate.

No. of teeth Z: 4

Helix angle: 30 degrees

No. of teeth Z: 4

Flute length L_c : 18 mm

Overhang length L_1 incl. recess: 44 mm

Recess $\varnothing D_1$: 13.5 mm

Overall length L: 83 mm

Shank $\varnothing D_s$: 14 mm

Technical description

Feed f_z for copy milling in steel < 900 N/mm ²	0.12 mm
Cutting edge $\varnothing D_c$	14 mm
No. of teeth Z	4
Flute length L_c	18 mm
Recess $\varnothing D_1$	13.5 mm
Overall length L	83 mm
Shank $\varnothing D_s$	14 mm

Overhang length L_1 incl. recess	44 mm
Helix angle	30 degrees
Feed f_z for side milling in steel < 900 N/mm ²	0.1 mm
Radius R	7 mm
Series	GARANT Master Steel
Coating	TiAlN
Tool material	Solid carbide
Standard	Manufacturer's standard
Type	N
Tolerance nominal \varnothing	f8
Direction of infeed	horizontal, oblique and vertical
Cutting width a_e for milling operation	0.03×D for copy milling
Cutting width a_e for milling operation	Full slot cutting depth 1×D
Shank	DIN 6535 HA to h6
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	End mill