

Garant
Solid carbide Woodruff keyseating cutter, TiAlN, Ø DC × LC h11 × e8: 10,5X3 mm

Order data

Order number	208024 10,5X3
GTIN	4062406397029
Item class	11X

Description
Version:

With new high-performance coating for very long tool life. Peripheral cutting, alternate set teeth (staggered). The sides of the teeth are ground to give clearance

Note:

Suitable for milling Woodruff keyways to DIN 6888.

Slot milled from solid: f_z for $a_p = 0.25 \times D$.

Type: N

No. of teeth Z: 6

No. of teeth Z: 6

for Woodruff keyways to DIN 6888: 3.0×3.7 mm

Recess Ø D_1 : 4.2 mm

Overall length L: 50 mm

Shank Ø D_s : 6 mm

Feed f_z for slot milling in steel < 900 N/mm²: 0.035 mm

Technical description

for Woodruff keyways to DIN 6888	3.0×3.7 mm
Cutting edge Ø D_c	10.5 mm
No. of teeth Z	6
Shank Ø D_s	6 mm
Overall length L	50 mm

Feed f_z for slot milling in steel < 900 N/mm ²	0.035 mm
Type	N
Recess $\varnothing D_1$	4.2 mm
Flute length L_c	3 mm
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 850 D/F
Milling profile	staggered teeth
Tolerance nominal \varnothing	e8
Direction of infeed	horizontal
Cutting width a_e for milling operation	Full slot cutting depth 1xD
Shank	DIN 6535 HB to h6
Through-coolant	no
Shank tolerance	h6
Corner chamfer angle	90 degrees
Colour ring	green
Type of product	End mill