

**Garant**
**Solid carbide Woodruff keyseating cutter, TiAlN, Ø DC × LC h11 × e8: 28,5X5 mm**

**Order data**

Order number	208024 28,5X5
GTIN	4062406397128
Item class	11X

**Description**
**Version:**

**With new high-performance coating** for very long tool life. Peripheral cutting, alternate set teeth (staggered). The sides of the teeth are ground to give clearance

**Note:**

Suitable for milling Woodruff keyways to DIN 6888.

Slot milled from solid:  $f_z$  for  $a_p = 0.25 \times D$ .

Type: N

No. of teeth Z: 10

No. of teeth Z: 10

for Woodruff keyways to DIN 6888: 5,0×11,0 mm

Recess Ø D<sub>1</sub>: 8.5 mm

Overall length L: 63 mm

Shank Ø D<sub>s</sub>: 10 mm

Feed  $f_z$  for slot milling in steel < 900 N/mm<sup>2</sup>: 0.04 mm

**Technical description**

Cutting edge Ø D <sub>c</sub>	28.5 mm
Type	N
No. of teeth Z	10
for Woodruff keyways to DIN 6888	5,0×11,0 mm
Recess Ø D <sub>1</sub>	8.5 mm

Overall length L	63 mm
Shank $\varnothing D_s$	10 mm
Feed $f_z$ for slot milling in steel < 900 N/mm <sup>2</sup>	0.04 mm
Flute length $L_c$	5 mm
Coating	TiAlN
Tool material	Solid carbide
Standard	DIN 850 D/F
Milling profile	staggered teeth
Tolerance nominal $\varnothing$	e8
Direction of infeed	horizontal
Cutting width $a_e$ for milling operation	Full slot cutting depth 1xD
Shank	DIN 6535 HB to h6
Through-coolant	no
Shank tolerance	h6
Corner chamfer angle	90 degrees
Colour ring	green
Type of product	End mill